

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-053160

(43)Date of publication of application : 25.02.2003

B01D 65/02

BOLD 61/20

(71)Applicant : MITSUBISHI RAYON CO LTD

(72)Inventor : TAKEDA SATORU

WATARI KENJI


SUEYOSHI SHINYA

(54) CLEANING METHOD FOR SEPARATING MEMBRANE AND MEMBRANE FILTERATER

(57)Abstract

PROBLEM TO BE SOLVED: To provide a method which is capable of efficiently cleaning a separating membrane and membrane filter which is capable of efficiently cleaning the separating membrane.

SOLUTION: If the separating membrane is cleaned by water for back washing stored in an accumulation tank disposed on a secondary side after the raw water on the primary side of the separating membrane is drained, the separating membrane can be efficiently cleaned. The effect is higher if pressurized gas is supplied into the accumulation tank and the separating membrane is back washed after the pressure is increased. The cleaning can be cost effectively and efficiently performed if the filtrate water of the separating membrane is used as the water for back washing and the volume of the water for back washing is set at 0.1 to 10 L per 1 m² of the area of the separating membrane.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the

<http://www19.ipdl.ncipi.go.jp/PAI/result/detail/main/wAAAXMa4BdDA415053160P4.htm>

11/1/2004

BEST AVAILABLE COPY